



NOTES:

- 1 : GROUPS – IIA & IIB AS PER IS 2148/1981 & IS 2206(PART-1)1984
- 2 : DEGREE OF PROTECTION – IP 65 AS PER IS 2147/1962
- 3 : MATERIAL – CAST ALUMINIUM ALLOY LM6
- 4 : EARTHING – ONE INTERNAL & TWO EXTERNAL SCREWS ARE PROVIDED
- 5 : GASKET – NEOPRENE
- 6 : FINISH – LIGHT GREY TO SHADE 631 OF IS:5
- 7 : CABLE ENTRY – 2 Nos. 3/4” ET ENTRY
- 8 : GLASS – HEAT RESISTANT TOUGHENED TYPE–A BOROSIL MAKE
- 9 : M.S.WIREGUARD – Ø5mm EPOXY WHITE PAINTED.
- 10 : LAMP HOLDER – ES HOLDER.
- 11 : CHOKE – POLYSTER FILLED COPPER WOUND CHOKE
- 12 : CAPACITOR – 1 No. 20mfd

OVERALL DIMENSION : ±10mm

CUSTOMER		TITLE					
PROJECT		FLP-WP INTEGRAL WELL GLASS FITTING SUITABLE FOR 250W HPMV LAMP					
CONSULTANT							
DRAWN	SM	SCG Ex d TECH PVT. LTD. CHENNAI-600 032					
CHECKED	DKK						
APPROVED	GK						
SCALE	NTS	FILE REF. LF/1235	CAT.NO. SC/991235	CMRS CERT No. CMRI/TC/P/H1217 Dt. 15.10.98	GA.DRG.No. SCG/OF0000/LF1235/0001	REV. 0	DATE 14/11/05