



DESCRIPTION	A	B	C	D	
20 W. DOUBLE	2'	1020	906	370	100
40 W. DOUBLE	4'	1630	1505	370	100

NOTES :

- 1 : GROUPS - IIA & IIB AS PER IS:2148/1981 & IS:2206 (PART -II) 1976.
- 2 : DEGREE OF PROTECTION - IP-65 AS PER IS : 2147/1962.
- 3 : MATERIAL - CAST ALUMINIUM ALLOY LM6.
- 4 : EARTHING 1 No. INTERNAL & 2 Nos. EXTERNAL SCREW SIZE M6.
- 5 : GASKET - NEOPRENE
- 6 : FINISH - LIGHT GREY EPOXY SHADE No. 631 OF IS:5.
- 7 : CABLE ENTRIES - 2 Nos. 3/4" ET
- 8 : GLASS - HEAT RESISTANT BOROSIL MAKE.
- 9 : WIREGUARD - M.S. 5mm ϕ WIRE WHITE EPOXY POWDER COATED
- 10 : REFLECTOR - M.S. EPOXY POWDER COATED.

OVERALL DIMENSION : ± 10 mm

CUSTOMER		TITLE :- FLP-WP FLUORESCENT LIGHT FITTING (DOUBLE)					
PROJECT		SCG Ex d TECH PVT. LTD. CHENNAI-600 032					
CONSULTANT							
DRAWN	SM						
CHECKED	DKK						
APPROVED	GK						
SCALE	NTS	FILE REF. LF/1271	CAT.NO. SC/991271	CMRS CERT No. CMRI/TC/H4 DATE 10.08.94.	GA.DRG.No. SCG/OF0000/LF1271/0001	REV. 0	DATE 14/11/05