



**NOTES :**

- 1 : FLP GROUPS – IIA & IIB AS PER IS:2148/1981 & IS:13947 (PART-I) 1993
- 2 : WEATHERPROOF – IP65 AS PER IS:2147
- 3 : MATERIAL – CAST ALUMINIUM ALLOY LM6
- 4 : EARTHING – 1 INTERNAL & 2 EXTERNALS SCREWS ARE PROVIDED
- 5 : GASKET – NEOPRENE "O" RING TYPE
- 6 : FINISH – LIGHT GREY TO SHADE 631 OF IS:5 (EPOXY POWDER COATED)
- 7 : TERMINAL BLOCKS – 4 Nos. 2.5 Sq.mm
- 8 : CABLE ENTRY – 3 Nos. 3/4"ET
- 9 : HEAT RESISTANT & TOUGHENED GLASS TYPE-"A" IS USED
- 10 : IT IS SUITABLE FOR 3x13W, 3x18W & 3x26W CFL LAMP.

**SPECIAL NOTES**

ALTERNATE VARIATIONS CAN BE OBTAINED FOR  
200W GLS / 160W MLL / 80 OR 125W OR METAL HALIDE LAMP

OVERALL DIMENSION : ±10mm

CUSTOMER		TITLE					
PROJECT		FLP – WP CFL LAMP BULK HEAD FITTING					
CONSULTANT		SCG Ex d TECH PVT. LTD.					
DRAWN	SM	CHENNAI-600 032					
CHECKED	DKK						
APPROVED	GK						
SCALE	NTS	FILE REF. LF/124	CAT.NO. SCG/BH/99124	CMRS CERT No. CMRI/TC/P/H560 DATED 30.05.00	GA.DRG.No. SCG/OF0000/LF124/0001	REV. 0	DATE 14/11/05