



**NOTES:**

- 1 : GROUPS – IIA & IIB AS PER IS 2148/1981 & IS 2206 (PART-II) 1976.
- 2 : DEGREE OF PROTECTION – IP 66 AS PER IS 2147/1962
- 3 : MATERIAL – CAST ALUMINIUM ALLOY LM6
- 4 : EARTHING – ONE INTERNAL & TWO EXTERNAL SCREWS ARE PROVIDED
- 5 : GASKET – NEOPRENE
- 6 : FINISH – LIGHT GREY TO SHADE 631 OF IS:5
- 7 : CABLE ENTRY – 1 No. 3/4” ET ENTRY
- 8 : GLASS – HEAT RESISTANT TOUGHENED BOROSIL MAKE
- 9 : M.S.WIREGUARD –  $\phi$ 5mm EPOXY WHITE PAINTED.
- 10 : LAMP HOLDER – BAKELITE HOLDER.

OVERALL DIMENSION :  $\pm 10$ mm

CUSTOMER		TITLE					
PROJECT		<b>FLP-WP EMERGENCY TUBELIGHT FITTING FOR SINGLE 05/06/08/11/20W TUBE LAMPS</b> <b>SCG Ex d TECH PVT. LTD.</b> <b>CHENNAI-600 032</b>					
CONSULTANT							
DRAWN	SM						
CHECKED	DKK						
APPROVED	GK						
SCALE	NTS	FILE REF. LF/163	CAT.NO. ETL/99163	CMRS CERT No. CMRI/TC/H892 DATE 07.07.97	GA.DRG.No. SCG/OF0000/LF163/0001	REV. 0	DATE 14/11/05